

File E67774
Project 04CA29187

July 10, 2004

REPORT

On

COMPONENT - SWITCHES, SPECIAL USE

Shin Chin Industrial Co Ltd
Tainan Taiwan

Copyright © 2004 Underwriters Laboratories Inc.

Underwriters Laboratories Inc. authorizes the above-named company to reproduce this Report provided it is reproduced in its entirety.

Underwriters Laboratories Inc. authorizes the above-named company to reproduce the latest pages of that portion of this Report consisting of this Cover Page through Page 3.

DESCRIPTION

GENERAL:

Section General of this Procedure file must be used as a supplement to this Descriptive Section. It contains information describing requirements for components and construction for products described in this section.

PRODUCT COVERED:

USR, CNR Component - Special-Use Switches.

Cat No.	Electrical Ratings	Temp °C	POL/ THR	PP	ENDUR	SPCOA
R13-915	1/4 hp / 250 V ac, 5 A / 125 V ac	65	1/1	--	6,000	--

EXPLANATION OF PRODUCT COVERED TABLE:

Abbreviations f/b - followed by
if ww/o - with or without
used Res. - Resistive load. 98-100 percent power factor.

POL/THR - No. of Poles/No. of Throws. "M" stands for Multi-Pole or Multi-Throw, e.g. 2/M indicates 2 Pole, Multi-Throw.

PP - "PP" Stands for Per Pole. PP in this column indicates that each pole is capable of switching the rated current.

ENDUR - Endurance Rating

SPCOA - Special Conditions of Acceptability; the applicable special COAs are indicated in this column in number form. The corresponding COAs are given in the following pages.