



PRODUCT CERTIFICATE

No.: CQC02001002126

NAME AND ADDRESS OF THE APPLICANT

DONGGUAN SANYOU ELECTRICAL APPLIANCES CO., LTD.
No.62, Tangpuxi Road, Puxinhu, Tangxia Town, Dongguan City, Guangdong, China

NAME AND ADDRESS OF THE MANUFACTURER

DONGGUAN SANYOU ELECTRICAL APPLIANCES CO., LTD.
No.62, Tangpuxi Road, Puxinhu, Tangxia Town, Dongguan City, Guangdong, China

NAME AND ADDRESS OF THE FACTORY

DONGGUAN SANYOU ELECTRICAL APPLIANCES CO., LTD. (V000883)
No.62, Tangpuxi Road, Puxinhu, Tangxia Town, Dongguan City, Guangdong, China

NAME, MODEL AND SPECIFICATION

Relay

SRD、SRDI系列 触点负载: 17A 125、250/277VAC(A型、C型常开端, 仅AgSnO₂、AgNi触点), 12A 250VAC、12A 277VAC (A型、C型常开端, 仅AgSnO₂、AgNi触点), 10A 250VAC (A型、C型常开端), 10A 277VAC、7A 277VAC、5A 277VAC(仅AgNi触点), 7A 250VAC, 5A 240VAC; SRDV系列 触点负载: 10A 250VAC (A型、C型常开端), 7A 250VAC, 5A 240VAC; SRU、SRDH系列 触点负载: 10A 250VAC; 线圈: 3VDC、5VDC、6VDC、9VDC、12VDC、15VDC、18VDC、24VDC、48VDC、60VDC; 线圈功耗: D-0.36W、D-0.45W(仅SRU)、H-1.06W (仅SRU)、L-0.36W(仅SRU); 电气寿命: 20000周期; 机械寿命: 50000周期; 环境温度: -40°C~105°C; RT II、RT III(系列命名方式见证书附件)

THE STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB/T21711.1-2008

CERTIFICATION MODEL

Type Testing of Product + Initial Factory Inspection + Follow up Factory Inspection


This is to certify that the above mentioned products have met the requirements of certification rules CQC11-462155-2010.

Date of issue: Aug.24,2015

Validity of this certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Date of original certification: Nov.21,2002

President:


Wang Kejiao



CHINA QUALITY CERTIFICATION CENTRE

Section 9, No.188, Nansihuan Xilu, Beijing 100070 P.R.China
<http://www.cqc.com.cn>

C 0062409



产品认证证书

附录:

第 1 页 共 1 页

证书编号: CQC02001002126

纸号: 62409

型号命名规则							
SRDI	-S	-1	12	D	M	1	-F-XX
特殊参数: 无-标准型, L-低温型, 其它字母或数字特殊要求							
绝缘等级: 无-普通型, B-Class B, F-Class F							
触点材质: 空-AgSnO ₂ ; 1-AgCdO (仅SRU, SRDH, SRDV系列) (以下仅SRD和SRDI系列)							
动点				静点			
空-AgSnO ₂ φ2.8(From C)				AgSnO ₂ φ3.0			
AgSnO ₂ φ3.0(From A或From B)							
1-AgCdOφ2.8				AgCdOφ3.0			
2-AgSnO ₂ φ2.8(From A或From B)				AgSnO ₂ φ3.0			
AgSnO ₂ φ3.0(From C)							
3-AgCdOφ3.0				AgCdOφ3.0			
4-三复合φ3.0				AgSnO ₂ φ3.0			
5-铜铍铜φ3.0				铜铍铜φ3.0			
6-AgNi				AgNi			
触点形式: 无-Form C, B-Form B, M-Form A							
线圈功耗: D-0.36W; D-0.45W(仅SRU) H-1.06W(仅SRU); L-0.36W(仅SRU)							
线圈规格 (VDC): 03,05,06,09,12,15,18,24,48,60							
触点组数: 1-1组							
封装形式: S-塑封式, SH-防水式							
基本型号: SRD, SRDI, SRU, SRDH, SRDV							

注: 此附录与证书同时使用时有效。

主任: _____



中国质量认证中心

中国·北京·南四环西路 188 号 9 区 100070

<http://www.cqc.com.cn>