




COVER



Specification:

Material:

1. JACK Housing :PC/ABS
UL94-V0,BLACK
2. RJ45 contact material & finished:
 - 2-1.Phosphor Bronze with Nickel plated.
 - 2-2.Contact area :Gold plated.

3.IDC Housing: PC, UL94-V0

4.IDC Terminal material & finished:

- 4-1.Phosphor Bronze with Tin plated.
- 4-2. 110 tool compatible.
- 4-3. Suitable for 22-26 AWG stranded and solid wire.

Performance:

- a.The sticker color codes combine two wirings of T568A & T568B.
- b.Insertion Force: 900 gms for 8 contacts.
- c.Retention Strength: 7.7 kgs between Jack and Plug.
- d.Operation Temperature: -20° to 68°.

e.Durability:

- e-1. Jack : 750 cycles Plug-Jack mating and unmating test, Insertion cycles at 20 cycles/minute max. Contact resistance test per 100 cycles.
- e-2. IDC : Max. 200 punching times.

f.The Cat.6 performance is in compliance with the ANSI/TIA/EIA 568 C standard.

			Tolerance: .X ±0.5 .X ±0.3 .XX ±0.10	SCALE: FREE	CUSTOMER :				Approved by
			Angle: X° ±3° .X° ±1°	UNIT: mm	CUSTOMER P/N:		COMPANY P/N: 01.075.0079		Checked by
REV.	DESCRIPTION	DATE	REV. : OO		DWG. No. :		TITLE: UTP CAT6 KEYSTONE JACK,180°		Design by XJH