

## PIN OUT

CN1 (568B)	CN2 (568B)
WHITE/ORANGE 1	1 WHITE/ORANGE
ORANGE 2	2 ORANGE
WHITE/GREEN 3	3 WHITE/GREEN
GREEN 6	6 GREEN
BLUE 4	4 BLUE
WHITE/BLUE 5	5 WHITE/BLUE
WHITE/BROWN 7	7 WHITE/BROWN
BROWN 8	8 BROWN

## NOTE:


1. Electrical test:

(1). 100% open short &amp; miss wire test;

(2). Insulation resistance: DC 300V 10M $\Omega$ ;(3). Contactor resistance: 3 $\Omega$ ;

2. RoHS compliant

## MATERIAL LIST:

DRAW NO.					PRODUCT NAME		CAT.6 UTP 8P8C - 8P8C		
①	CABLE	Cat.6 7/0.16CU *4P UTP JACKET:PVC	OD:5.7 $\pm$ 0.1mm	1	CUSTOMER	VIEW	Tolerance		
②	PVC	75A PVC		2	ITEM NO.		X.	$\pm 1.00$	
③	8P8C PLUG	RJ45 8P8C PLUG, CAT.6 UTP Pin GOLD 3U", Circle Type. Take 6 under 2 stent		2	APPOBY	CHECKBY	DRAWNBY	UNIT	MM
NO.	PARTS NAME	SPECIFICATION DESCRIPTION			QT" Y	REMARK		Page	1 of 1