



PIN OUT

CN1 (568B)		CN2 (568B)
WHITE/ORANGE 1		1 WHITE/ORANGE
ORANGE 2		2 ORANGE
WHITE/GREEN 3		3 WHITE/GREEN
GREEN 6		6 GREEN
BLUE 4		4 BLUE
WHITE/BLUE 5		5 WHITE/BLUE
WHITE/BROWN 7		7 WHITE/BROWN
BROWN 8		8 BROWN

NOTE:

1. Electrical test:

(1). 100% open short & miss wire test;

(2). Insulation resistance: DC 300V 3M Ω ;(3). Contactor resistance: 3 Ω ;

2. RoHS compliant

MATERIAL LIST:

					DRAW NO.	PRODUCT NAME	CAT. 5E UTP 8P8C - 8P8C		
①	CABLE	Cat. 5e 7/0.16 CU *4P UTP JACKET: PVC	OD: 5.0 \pm 0.2mm	1	CUSTOMER	VIEW	Tolerance		
②	PVC	75A PVC		2	ITEM NO.		X.	\pm 1.00	
③	8P8C PLUG	RJ45 8P8C PLUG, CAT. 5e UTP Pin GOLD 3U*, Circle Type.		2	APPOBY	CHECKBY	DRAWNBY	UNTT	MM
NO.	PARTS NAME	SPECIFICATION DESCRIPTION		QT* Y	REMARK				Page 1 of 1