



## PIN OUT

CN1 (568B)		CN2 (568B)
WHITE/ORANGE 1	↔	1 WHITE/ORANGE
ORANGE 2	↔	2 ORANGE
WHITE/GREEN 3	↔	3 WHITE/GREEN
GREEN 6	↔	6 GREEN
BLUE 4	↔	4 BLUE
WHITE/BLUE 5	↔	5 WHITE/BLUE
WHITE/BROWN 7	↔	7 WHITE/BROWN
BROWN 8	↔	8 BROWN

## NOTE:

1. Electrical test:

(1). 100% open short &amp; miss wire test;

(2). Insulation resistance: DC 300V 10MΩ;

(3). Contact resistance: 3Ω;

2. RoHS compliant

## MATERIAL LIST:

				DRAW NO.	PRODUCT NAME	CAT.6 UTP 8P8C - 8P8C			
①	CABLE	Cat.6 7/0.16CU *4P UTP JACKET:PVC	OD:5.7 ±0.1mm	1	CUSTOMER	VIEW	Tolerance		
②	PVC	75A PVC		2	ITEM NO.		X.	±1.00	
③	8P8C PLUG	RJ45 8P8C PLUG, CAT.6 UTP Pin GOLD 3U", Circle Type. Take 6 under 2 stent		2	APPOBY	CHECKBY	DRAWNBY	UNTT	MM
NO.	PARTS NAME	SPECIFICATION DESCRIPTION		QT'Y	REMARK			Page	1 of 1