



## PIN OUT

CN1 (568B)	CN2 (568B)
WHITE/ORANGE 1	1 WHITE/ORANGE
ORANGE 2	2 ORANGE
WHITE/GREEN 3	3 WHITE/GREEN
GREEN 6	6 GREEN
BLUE 4	4 BLUE
WHITE/BLUE 5	5 WHITE/BLUE
WHITE/BROWN 7	7 WHITE/BROWN
BROWN 8	8 BROWN

## NOTE:

1. Electrical test:

(1). 100% open short &amp; miss wire test;

(2). Insulation resistance: DC 300V 10M  $\Omega$ ;(3). Contact resistance: 3  $\Omega$ ;

2. RoHS compliant

## MATERIAL LIST:

				DRAW NO.	PRODUCT NAME	CAT.6 UTP 8P8C - 8P8C		
①	CABLE	Cat.6 7/0.16CU *4P UTP JACKET:PVC	OD:5.7 $\pm$ 0.1mm	1	CUSTOMER	VIEW	Tolerance	
②	PVC	75A PVC		2	ITEM NO.		X. $\pm$ 1.00	X.X $\pm$ 0.50
③	8P8C PLUG	RJ45 8P8C PLUG, CAT.6 UTP Pin GOLD 3U", Circle Type. Take 6 under 2 stent		2	APPOBY	CHECKBY	DRAWNBY	UNTT MM
NO.	PARTS NAME	SPECIFICATION DESCRIPTION		QT'Y	REMARK			Page 1 of 1