USB DOCKING STATION with FAN VE 534

Ιδανική λύση για ταυτοχρονη ψύξη του φορητού σας αλλά & κάλυψη όλων των απαραίτητων θύρων χωρίς την αγορά των επιπλέον μετατροπεων. Κατασκευασμένο από αλουμίνιο,συμβατό με USB 2.0 προδιαγραφες & τροφοδοσία με adaptor ρευματος 5V

VIEWCON®

USB2.0 to DVI : USB specification revision 2.0/1.1 compliant
Resolution Supported DVI: 640x480, 720x480, 768x576, 800x600, 1024x768, 1280x720, 1280x1 024,1360x768, 1366x768, 1440x900, 1600x1200,1680x1050
Function supported: **1.** Primary **2.** Extended **3.** Mirror **4.** Rotate
Operating System Supported: Windows 2000 Sp4, XP Sp2/ Vista 32-bit/ Win7, Mac os

USB to Parallel: USB specification revision 1.1 compliant
Truly Bi-dorectional communication between PC & printer
Support Win98/ 2000/ XP/ Vista/ Win7, Mac OS v8.6-9.2

USB2.0 to Rs232: USB specification revision 2.0/1.1 compliant
Support RS232 serial interface
Support over 1 Mbps data transfer rate
Support remote wake-up and power management
Support Win98/ 98SE/ ME/ 2000/ XP/ Vista/ Win7, Mac OS

USB Audio: USB specification revision 2.0/1.1 compliant
Compliant with USB Audio Device Class Specification v1.0
Support Xear 3D
Support Win2000/ 2003/ XP/ Vista/ Win7, Mac OS9.0x or higher

USB 2.0 to Fast Ethernet: Support TCP/IP,NetBEUI,IPXISPX protocols
Support USB suspend/resume detection logic & wake-up frame
Support WinCE/ 98/ 2000/ XP/ Vista / Win7

USB to PS/2: USB specification revision 2.0/1.1 compliant
Support Windows & multimedia keyboard
Support 3D3K Wheel mouse & optical mouse
Support PS/2 keyboards or PS/2 mouses at the same time
Support Win98/ ME/ 2000/ XP/ Linux/ Vista/ Win7,Mac os

USB2.0: Compliant with USB Specification Revision 2.0
Support high speed 480Mbps, full speed 12Mbps low speed 1.5Mbps
Hot swappable, plug & play
Support WIN2000/ XP/ VISTA/ Windows 7, MAC OS

FAN: Bearing type: Sleeve bearing
Rated voltage: DC 5V
Rated Current: DC0.20A(±10%)
Rated speed: 3500RPM(±10%)
Max.airflow:2.50CFM(± 10%)
Noise level:26DB
Durability: up to 30000 hours(25°C relative humidity 45-85%)